

# HENSEL

■ ■ ■ ■ ■ PERFORMING LIGHT

## INTEGRA PLUS

250

500

1000



## PROVEN AND RELIABLE.

- SHORT FLASH DURATION AND FAST RECYCLING TIMES
- WIDE POWER RANGE
- RADIO SYNC AND REMOTE CONTROL
- INTEGRATED FREEMASK FUNCTION FOR QUICK CUT-OUTS
- COMPREHENSIVE ACCESSORY PROGRAM
- STURDY & HIGH-QUALITY DIE-CAST ALUMINUM HOUSING



■ ■ ■ ■ ■ MADE IN GERMANY

## INTEGRA PLUS. FOR COUNTLESS APPLICATIONS.

Hensel compact flash units are known for their reliability and longevity. Many Hensel flashes have been serving reliably in professional photo studios for decades. The current Integra Plus flash units are also nearly indestructible tools for daily use – they are modern classics.

This series purposely comes without any gadgets. Instead, the main focus was on ease of use and absolute reliability. So, it is no wonder that many portrait studios, product photographers, and also numerous institutes, schools, and public offices count on Integra Plus compact flashes. The integrated Strobe Wizard Plus radio sync and remote control ease the work. Cut-outs are done incredibly easy and fast via the optional “Mask Integrator” software and if desired, even automatically.

Thanks to a setting range of 6 f-stops and a comprehensive selection of light shaping tools, many photographic projects can be realized with Integra Plus flash units. The popular and sturdy Hensel EH quick-change system eases and speeds up light former mounting. Even large softboxes can quickly and easily be changed by just one person.

And last but not least, the Hensel Flash system has been continuously maintained guaranteeing professional service for many years and for all equipment – just in case something should happen. This too, makes the Integra Plus series a great buy – it’s technology you can count on.

CODE NO.	8814FM	8815FM	8816FM
ENERGY	250-8 Ws	500-16 Ws	1000-32 Ws
F-STOP IN 1M/ISO 100 WITH 12" REFLECTOR	45 8/10	64 8/10	90 9/10
MIN. FLASH DURATION TIME (T 0.5)	1/2.400 sec.	1/1.400 sec.	1/1.700 sec.
MAX. FLASH DURATION TIME (T 0.5)	1/1.200 sec.	1/700 sec.	1/700 sec.
FLASH RECYCLING TIMES, MIN. POWER	0.3 sec.	0.5 sec.	0.45 sec.
FLASH RECYCLING TIMES, MAX. POWER	1.3 sec.	1.9 sec.	2.1 sec.
POWER RANGE	6 f-stops in 1/10 steps	6 f-stops in 1/10 steps	6 f-stops in 1/10 steps
MODELING LIGHT	300 W/G 6.35 on/off/full/prop.	300 W/G 6.35 on/off/full/prop.	300 W/G 6.35 on/off/full/prop.
MAINS VOLTAGE	110V/60Hz and 240V/50Hz	110V/60Hz and 240V/50Hz	110V/60Hz and 240V/50Hz
SYNCHRONIZATION	radio, 6.3mm plug & photocell (w/switch-off)	radio, 6.3mm plug & photocell (w/switch-off)	radio, 6.3mm plug & photocell (w/switch-off)
REMOTE CONTROL	Strobe Wizard Plus	Strobe Wizard Plus	Strobe Wizard Plus
READY INDICATOR	acoustic, visual & flash check	acoustic, visual & flash check	acoustic, visual & flash check
REFLECTOR CONNECTOR	Hensel EH quick-change system	Hensel EH quick-change system	Hensel EH quick-change system
PROTECTIVE GLASS	included	included	included
WEIGHT	2.75 kg	2.87 kg	3.9 kg
DIMENSIONS (LXWXH)	33x15x23 cm	33x15x23 cm	39.5x15x23 cm
EXTRAS	Freemask function for auto. cut-outs, umbrella holder, Battery operation with opt. Power Max L	Freemask function for auto. cut-outs, umbrella holder, Battery operation with opt. Power Max L	Freemask function for auto. cut-outs, umbrella holder, Battery operation with opt. Power Max L

## STURDY METAL HOUSINGS.

